



# ONE Cut

Micro fine abrasive paste incl. sealing

servFaces ONE Cut is a silicone-free polish for professional reconditioning of lightly to moderately scratched painted surfaces in one step. Thanks to its special high-performance abrasive particles, the polish is also ideally suited to scratch-resistant clear coats. It quickly removes medium surface scratches and sanding from grit P2500 or other similar signs of use with a high-gloss and hologram-free finish. ONE Cut is ideally suited to the quick preparation of painted surfaces, such as the preparation of used sales vehicles. Thanks to the integrated sealing components, it additionally protects the paint surface, which is why no further work step is required.

## Areas of application:

Suitable for paints on cars, motorcycles, commercial vehicles, etc.

## Properties:

Grinding grade: 8.0

Gloss grade: 11.0

## Use:

Apply servFaces ONE Cut evenly to the surface to be treated and pre-polish using a free-running or positively driven eccentric polishing machine and a servFaces polishing sponge V3, HSC-Medium Cut or HSC-Fine Cut polishing sponge (for grit size P2500 or higher) in a crosswise motion at low to medium speed and medium pressure. After about 40-60 seconds, increase the speed and the contact pressure to remove the polish. To remove polish residues, it is best to use a microfiber cloth such as the servFaces Premium Buffing Towel or the Premium Allround Towel.

**TIP:** For dark and sensitive paint surfaces, you should use a free-running eccentric polisher. For optimum results, the polishing sponges used have to be of an open-cell, fine to medium cell structure, as otherwise the abrasive particles in the polish will not break down and therefore not produce a hologram-free finish.

**Note:** Make sure you apply the correct amount. Using too much polish can result in sanding marks, as the abrasives then take too long to break down and therefore you will not achieve a good finish. Please note that the ONE Cut is not suitable for paint preparation before applying paint coatings!

**Caution: Do not apply the product in direct sunlight and do not let it dry!**

## Warning:

Shake well before use. Check for suitability and compatibility before use. Do not apply to hot surfaces and protect from excessive heat and frost.

---

**Application temperature:**  
+10°C to +30°C

**Storage temperature:**  
+10°C to +25°C

**Consumption:**  
6 to 10 ml per m<sup>2</sup>

**pH:**  
Not determined

## Storage and shelf life:

At least 12 months at room temperature in tightly sealed original container.

**Protect from direct sunlight and freezing temperatures!**

---

## Container sizes:

Art. No.:	Container:
SF10425	250 ml
SF10425.1	1000 ml



**Accessories:**

HSC Medium Cut Polishing Sponge, HSC Fine Cut Polishing Sponge, Polishing Sponge V3, Polishing Sponge RT/V3, Polishing Pad TS 5 PRO, Polishing Pad TS 7 PRO

For optimum results, the polishing sponges used must have an open-cell and fine to medium cell structure, otherwise the abrasive particles in the polish will not break down and therefore not produce a hologram-free finish.

This product information should and can only be taken as non-binding advice. The manufacturer does not accept any liability whatsoever. Before use, make sure that the product is suitable for your particular application.