



PPF & Film Application GEL - rtu

Ready-to-use installation gel for self-adhesive films

servFaces PPF & Film Application GEL is a transparent, medium-viscosity slip solution gel specifically designed to significantly simplify the application of paint protection films. This gel is characterized by its gel-like yet highly sprayable consistency, which allows for easy application using spray bottles and various spray applicators.

The formula of servFaces PPF & Film Application GEL is optimized so that the adhesives of the films being applied are not affected either in color or chemically. The gel ensures optimal wetting of the substrate, which guarantees the repositionability of the films during application and significantly simplifies the entire work process.

The servFaces PPF & Film Application GEL can also be removed effortlessly and without leaving any residue even when dry, guaranteeing clean and efficient application.

Application Areas:

- Painted surfaces
- Gelcoat surfaces
- Glass surfaces
- Plastics (including acrylic glass and polycarbonate)
- A wide variety of metal surfaces

Properties:

- Ready to use
- High viscosity
- Evaporates quickly after application
- Adheres well to horizontal and vertical surfaces
- Makes it easier to apply paint protection films

Application:

Spray the servFaces PPF & Film Application GEL (slip solution) evenly onto the surface until it is completely saturated. To make the film easier to handle, we recommend applying the gel to the adhesive side of the film as well. Then position the film in the desired area and apply a little more gel to the back of the film to create a lubricating film that makes it easier to smooth out the gel. Alternatively, you can also use the servFaces PPF & Film Application Fluid for this purpose.

Please note that paint protection films (PPF) require some time to develop their full adhesive strength and for the water contained in the gel to dry completely under the film. When folding the edges, the product must be rinsed with a tack solution (demineralized water / optionally with 3–5% isopropanol).

Warning: Do not use on hot surfaces!

Application temperature:
+5°C bis +40°C

Storage temperature:
+10°C bis +25°C

pH-value:
7,0 – 7,5

Storage and shelf life:
At least 24 months at room temperature in tightly sealed original containers

Warning: Protect the product from direct sunlight and frost!



Container sizes:

Item No.:	Size:
SF10501	750 ml
SF10501.1	5 liters
SF10501.2	25 liters

Accessories:

Item No.: SF10456 / Professional Hand Sprayer - 1.0 liter with special EPDM-seals

This product information should and can only be taken as non-binding advice. The manufacturer does not accept any liability whatsoever. Before use, make sure that the product is suitable for your particular application.