



Revision: 22.07.2026

Rim Coat 365
Product code: SF10515

Page 1 of 14

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Rim Coat 365

UFI: 4DP2-TQ2C-VH9G-M533

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

Automotive care products

1.3. Details of the supplier of the safety data sheet

Company name:	ServFaces GmbH	
Street:	Zeppelinstraße 2-4	
Place:	D-72488 Sigmaringen	
Telephone:	+49 7571 6894 0	
E-mail:	info@servfaces.de	
Contact person:	Jörg Reents	Telephone: +49 7571 6894 0
E-mail:	info@servfaces.de	
Internet:	www.servfaces.de	
Responsible Department:	Giftinformationszentrum Mainz / 24h Deutsch & Englisch	

1.4. Emergency telephone number:

+49 6131 / 19240 (24h)

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Regulation (EC) No 1272/2008**

Flam. Liq. 2; H225
Water-react. 3; H261
Acute Tox. 4; H302
Skin Corr. 1B; H314
Eye Dam. 1; H318
Skin Sens. 1; H317
Asp. Tox. 1; H304
Aquatic Chronic 4; H413

Full text of hazard statements: see SECTION 16.

2.2. Label elements**Regulation (EC) No 1272/2008****Hazard components for labelling**

Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics
Cyclosilazanes, di-Me, Me hydrogen, polymers with di-Me, Me hydrogen silazanes, reaction products with 3-(triethoxysilyl)-1-propanamine
Hydrocarbons, C11-C14, isoalkanes, cyclics, <2% aromatics
3-aminopropyltriethoxysilane

Signal word: Danger**Pictograms:****Hazard statements**

H225 Highly flammable liquid and vapour.



Safety Data Sheet

ServFaces GmbH

Rim Coat 365

Revision: 22.07.2026

Product code: SF10515

Page 2 of 14

H261	In contact with water releases flammable gases.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H413	May cause long lasting harmful effects to aquatic life.
EUH014	Reacts violently with water.
EUH029	Contact with water liberates toxic gas.

Precautionary statements

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P260	Do not breathe gas.
P280	Wear protective gloves/protective clothing and eye protection/face protection.
P405	Store locked up.
P501	Dispose of contents/container to an appropriate recycling or disposal facility.

2.3. Other hazards

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Relevant ingredients

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
	Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics			35 - < 40 %
	918-167-1		01-2119472146-39	
	Flam. Liq. 3, Asp. Tox. 1, Aquatic Chronic 4; H226 H304 H413 EUH066			
475645-84-2	Cyclosilazanes, di-Me, Me hydrogen, polymers with di-Me, Me hydrogen silazanes, reaction products with 3-(triethoxysilyl)-1-propanamine			20 - < 25 %
	Flam. Liq. 2, Water-react. 3, Acute Tox. 3, Skin Corr. 1B, Eye Dam. 1, Aquatic Chronic 3; H225 H261 H301 H314 H318 H412 EUH014 EUH029			
	Hydrocarbons, C11-C14, isoalkanes, cyclics, <2% aromatics			15 - < 20 %
	927-285-2		01-2119480162-45	
	Asp. Tox. 1; H304 EUH066			
123-86-4	n-butyl acetate			10 - < 15 %
	204-658-1	607-025-00-1	01-2119485493-29	
	Flam. Liq. 3, STOT SE 3; H226 H336 EUH066			
919-30-2	3-aminopropyltriethoxysilane			5 - < 10 %
	213-048-4	612-108-00-0	01-2119480479-24	
	Acute Tox. 4, Skin Corr. 1B, Eye Dam. 1, Skin Sens. 1; H302 H314 H318 H317			

Full text of H and EUH statements: see section 16.



Rim Coat 365

Revision: 22.07.2026

Product code: SF10515

Page 3 of 14

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
	918-167-1	Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics	35 - < 40 %
		inhalation: LC50 = 9,3 mg/l (dusts or mists); dermal: LD50 = > 5000 mg/kg; oral: LD50 = > 15000 mg/kg	
475645-84-2		Cyclosilazanes, di-Me, Me hydrogen, polymers with di-Me, Me hydrogen silazanes, reaction products with 3-(triethoxysilyl)-1-propanamine	20 - < 25 %
		oral: LD50 = 300 - 2000 mg/kg	
123-86-4	204-658-1	n-butyl acetate	10 - < 15 %
		inhalation: LC50 = > 21,1 mg/l (vapours); dermal: LD50 = > 14000 mg/kg; oral: LD50 = > 10000 mg/kg	
919-30-2	213-048-4	3-aminopropyltriethoxysilane	5 - < 10 %
		dermal: LD50 = 3800 mg/kg; oral: LD50 = 1780 mg/kg	

SECTION 4: First aid measures**4.1. Description of first aid measures****General information**

First aider: Pay attention to self-protection!
When in doubt or if symptoms are observed, get medical advice.

After inhalation

Provide fresh air. If experiencing respiratory symptoms: Call a doctor.

After contact with skin

Remove mechanically (e.g. dab away using wadding or cellulose material) then thoroughly wash the affected skin with a mild cleansing agent and water. Take off immediately all contaminated clothing and wash it before reuse. In case of skin reactions, consult a physician.

After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist. Remove contact lenses, if present and easy to do. Continue rinsing.

After ingestion

Observe risk of aspiration if vomiting occurs. Do NOT induce vomiting. If swallowed, rinse mouth with water (only if the person is conscious). When in doubt or if symptoms are observed, get medical advice.

4.2. Most important symptoms and effects, both acute and delayed

Allergic reactions

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

Carbon dioxide (CO₂). alcohol resistant foam. Dry extinguishing powder. Water mist.
Co-ordinate fire-fighting measures to the fire surroundings.

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Highly flammable liquid and vapour. Vapours can form explosive mixtures with air.
In contact with water releases flammable gases. (Hydrogen, Ammonia (NH₃))
In case of fire may be liberated: Pyrolysis products, toxic. (Carbon monoxide), Carbon dioxide (CO₂).

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus. Full protection suit.



Revision: 22.07.2026

Rim Coat 365
Product code: SF10515

Page 4 of 14

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures****General advice**

Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes.

For non-emergency personnel

Provide adequate ventilation. Use personal protection equipment.

For emergency responders

Personal protection equipment: see section 8

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up**For containment**

Stop leak if safe to do so. Cover drains.

For cleaning up

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

Ventilate affected area. Do not rinse down with water. (Formation of: Ammonia (NH₃), Hydrogen)

Other information

Use non-sparking tools.

Clean contaminated articles and floor according to the environmental legislation.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes.

Use personal protection equipment.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Use only antistatically equipped (spark-free) tools.

Advice on general occupational hygiene

Take off contaminated clothing. Draw up and observe skin protection programme. Wash hands before breaks and after work. When using do not eat, drink, smoke, sniff.

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Keep container tightly closed in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hints on joint storage

Do not store together with: Oxidizing agent. Pyrophoric or self-heating substances.

Further information on storage conditions

Keep away from heat. Protect from direct sunlight. Protect from moisture.



Rim Coat 365

Revision: 22.07.2026

Product code: SF10515

Page 5 of 14

7.3. Specific end use(s)

Automotive care products

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
7664-41-7	Ammonia, anhydrous	25	18		TWA (8 h)	WEL
		35	25		STEL (15 min)	WEL
123-86-4	Butyl acetate	150	724		TWA (8 h)	WEL
		200	966		STEL (15 min)	WEL

DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
123-86-4	n-butyl acetate			
Worker DNEL, long-term		inhalation	local	300 mg/m ³
Worker DNEL, acute		inhalation	systemic	600 mg/m ³
Worker DNEL, acute		inhalation	local	600 mg/m ³
Worker DNEL, long-term		inhalation	systemic	48 mg/m ³
Worker DNEL, long-term		dermal	systemic	7 mg/kg bw/day
Worker DNEL, acute		dermal	systemic	11 mg/kg bw/day
Consumer DNEL, long-term		inhalation	local	35,7 mg/m ³
Consumer DNEL, long-term		inhalation	systemic	12 mg/m ³
Consumer DNEL, acute		inhalation	systemic	300 mg/m ³
Consumer DNEL, acute		inhalation	local	300 mg/m ³
Consumer DNEL, acute		oral	systemic	2 mg/kg bw/day
Consumer DNEL, long-term		dermal	systemic	3,4 mg/kg bw/day
Consumer DNEL, acute		dermal	systemic	6 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	2 mg/kg bw/day
919-30-2	3-aminopropyltriethoxysilane			
Worker DNEL, long-term		inhalation	systemic	14 mg/m ³
Worker DNEL, long-term		dermal	systemic	2 mg/kg bw/day



Rim Coat 365

Revision: 22.07.2026

Product code: SF10515

Page 6 of 14

PNEC values

CAS No	Substance	
Environmental compartment		Value
123-86-4	n-butyl acetate	
Freshwater		0,18 mg/l
Freshwater (intermittent releases)		0,36 mg/l
Marine water		0,018 mg/l
Freshwater sediment		0,981 mg/kg
Marine sediment		0,0981 mg/kg
Microorganisms in sewage treatment plants (STP)		35,6 mg/l
Soil		0,0903 mg/kg
919-30-2	3-aminopropyltriethoxysilane	
Freshwater		0,5 mg/l
Freshwater (intermittent releases)		2,05 mg/l
Marine water		0,05 mg/l
Freshwater sediment		1,8 mg/kg
Marine sediment		0,18 mg/kg
Microorganisms in sewage treatment plants (STP)		0,81 mg/l
Soil		0,069 mg/kg

8.2. Exposure controls**Appropriate engineering controls**

Provide adequate ventilation as well as local exhaust at critical locations.

Individual protection measures, such as personal protective equipment**Eye/face protection**

Wear eye protection/face protection. EN ISO 16321 (EN 166)

Hand protection

Wear suitable gloves. (EN ISO 374)

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

Wear suitable protective clothing. Flame-retardant protective clothing. Wear anti-static footwear and clothing

Respiratory protection

Respiratory protection necessary at: insufficient ventilation, aerosol or mist formation, exceeding exposure limit values

Thermal hazards

Flame-retardant protective clothing. Wear anti-static footwear and clothing

Environmental exposure controls

Avoid release to the environment.



Revision: 22.07.2026

Rim Coat 365
Product code: SF10515

Page 7 of 14

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state:	Flüssig	
Colour:	colourless	
Odour:	like: Ammonia (NH ₃)	
Odour threshold:	not determined	
Melting point/freezing point:		not determined
Boiling point or initial boiling point and boiling range:		not determined
Flammability:	Highly flammable liquid and vapour.	
Lower explosion limits:		not determined
Upper explosion limits:		not determined
Flash point:		< 21 °C
Auto-ignition temperature:		not determined
Decomposition temperature:		not determined
pH-Value:		not determined
Viscosity / kinematic:		not determined
Water solubility:		Reacts with : Water.
Solubility in other solvents		
not determined		
Partition coefficient n-octanol/water:		not determined
Vapour pressure:		not determined
Density:		not determined
Relative vapour density:		not determined
Particle characteristics:		not applicable

9.2. Other information**Information with regard to physical hazard classes**

Explosive properties

Vapours can form explosive mixtures with air.

Further Information

No information available.

SECTION 10: Stability and reactivity**10.1. Reactivity**

Highly flammable.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Vapours can form explosive mixtures with air.

Reacts with : Water. Formation of: Ammonia (NH₃). Hydrogen.**10.4. Conditions to avoid**

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Protect from direct sunlight.

Protect from moisture.

10.5. Incompatible materials

Oxidizing agent. Pyrophoric or self-heating substances. Water.

10.6. Hazardous decomposition productsIn case of fire may be liberated: Carbon monoxide, Carbon dioxide (CO₂)., Pyrolysis products, toxic.



Rim Coat 365

Revision: 22.07.2026

Product code: SF10515

Page 8 of 14

In contact with water releases flammable gases. (Hydrogen, Ammonia (NH₃))**SECTION 11: Toxicological information****11.1. Information on hazard classes****Acute toxicity**

Harmful if swallowed.

Contact with water liberates toxic gas.

ATEmix calculated

ATE (oral) 1285 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
	Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics				
	oral	LD50 > 15000 mg/kg	Rat	Manufacturer	
	dermal	LD50 > 5000 mg/kg	Rabbit	Manufacturer	
	inhalation (4 h) dust/mist	LC50 9,3 mg/l	Rat	Manufacturer	
475645-84-2	Cyclosilazanes, di-Me, Me hydrogen, polymers with di-Me, Me hydrogen silazanes, reaction products with 3-(triethoxysilyl)-1-propanamine				
	oral	LD50 300 - 2000 mg/kg	Rat	Manufacturer	
123-86-4	n-butyl acetate				
	oral	LD50 > 10000 mg/kg	Rat	Manufacturer	
	dermal	LD50 > 14000 mg/kg	Rabbit	Manufacturer	
	inhalation (4 h) vapour	LC50 > 21,1 mg/l	Rat	Manufacturer	OECD 403
919-30-2	3-aminopropyltriethoxysilane				
	oral	LD50 1780 mg/kg	Rat	Manufacturer	
	dermal	LD50 3800 mg/kg	Rabbit	Manufacturer	

Irritation and corrosivity

Skin corrosion/irritation: Causes severe skin burns and eye damage.

Serious eye damage/eye irritation: Causes serious eye damage.

Sensitising effects

May cause an allergic skin reaction. (3-aminopropyltriethoxysilane)

Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.



Rim Coat 365

Revision: 22.07.2026

Product code: SF10515

Page 9 of 14

Aspiration hazard

May be fatal if swallowed and enters airways.

Information on likely routes of exposureEye contact, Skin contact, oral
aerosol or mist formation: Inhalation**11.2. Information on other hazards****Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

SECTION 12: Ecological information**12.1. Toxicity**

May cause long lasting harmful effects to aquatic life.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
475645-84-2	Cyclosilazanes, di-Me, Me hydrogen, polymers with di-Me, Me hydrogen silazanes, reaction products with 3-(triethoxysilyl)-1-propanamine					
	Acute fish toxicity	LC50 57,1 mg/l	96 h	Danio rerio (zebrafish)	Manufacturer	
123-86-4	n-butyl acetate					
	Acute fish toxicity	LC50 18 mg/l	96 h	Pimephales promelas (fathead minnow)	Manufacturer	
	Acute algae toxicity	ErC50 648 mg/l	72 h	Desmodesmus subspicatus	Manufacturer	
	Acute crustacea toxicity	EC50 44 mg/l	48 h	Daphnia magna (Big water flea)	Manufacturer	
	Crustacea toxicity	NOEC 23 mg/l	21 d	Daphnia magna (Big water flea)	Manufacturer	
919-30-2	3-aminopropyltriethoxysilane					
	Acute fish toxicity	LC50 934 mg/l	96 h	Danio rerio (zebrafish)	Manufacturer	OECD 203
	Acute algae toxicity	ErC50 603 mg/l	72 h	Desmodesmus subspicatus	Manufacturer	
	Acute crustacea toxicity	EC50 331 mg/l	48 h	Daphnia magna (Big water flea)	Manufacturer	OECD 202

12.2. Persistence and degradability

The product has not been tested.

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
123-86-4	n-butyl acetate			
	Regulation (EC) No. 440/2008, Annex C.5 (BOD)	80 %	5	Manufacturer
	Readily biodegradable (according to OECD criteria).			
919-30-2	3-aminopropyltriethoxysilane			
	Aerobic biological treatment	67 %	28	Manufacturer
	Not readily biodegradable (according to OECD criteria)			

12.3. Bioaccumulative potential

The product has not been tested.



Safety Data Sheet

Rim Coat 365

Revision: 22.07.2026

Product code: SF10515

Page 10 of 14

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
123-86-4	n-butyl acetate	1,82
919-30-2	3-aminopropyltriethoxysilane	0,31

BCF

CAS No	Chemical name	BCF	Species	Source
919-30-2	3-aminopropyltriethoxysilane	3,4	Cyprinus carpio (Common Carp)	Manufacturer

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No information available.

Further information

Avoid release to the environment.

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Disposal recommendations**

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste according to applicable legislation.

Contaminated packaging

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information**Land transport (ADR/RID)****14.1. UN number or ID number:**

UN 3129

14.2. UN proper shipping name:

WATER-REACTIVE LIQUID, CORROSIVE, N.O.S. (Cyclosilazanes, di-Me, Me hydrogen, polymers with di-Me, Me hydrogen silazanes, reaction products with 3-(triethoxysilyl)-1-propanamine)

14.3. Transport hazard class(es):

4.3

14.4. Packing group:

II

Hazard label:

4.3+8



Classification code:

WC1

Special Provisions:

274

Limited quantity:

500 mL

Excepted quantity:

E0

Transport category:

0

Hazard No:

382

Tunnel restriction code:

D/E

Inland waterways transport (ADN)



Safety Data Sheet

Rim Coat 365

Revision: 22.07.2026

Product code: SF10515

Page 11 of 14

14.1. UN number or ID number:

UN 3129

14.2. UN proper shipping name:

WATER-REACTIVE LIQUID, CORROSIVE, N.O.S. (Cyclosilazanes, di-Me, Me hydrogen, polymers with di-Me, Me hydrogen silazanes, reaction products with 3-(triethoxysilyl)-1-propanamine)

14.3. Transport hazard class(es):

4.3

14.4. Packing group:

II

Hazard label:

4.3+8



Classification code:

WC1

Special Provisions:

274

Limited quantity:

500 mL

Excepted quantity:

E0

Marine transport (IMDG)**14.1. UN number or ID number:**

UN 3129

14.2. UN proper shipping name:

WATER-REACTIVE LIQUID, CORROSIVE, N.O.S. (CYCLOSILAZANES)

14.3. Transport hazard class(es):

4.3

14.4. Packing group:

II

Hazard label:

4.3+8



Special Provisions:

274

Limited quantity:

0

Excepted quantity:

E0

EmS:

F-G, S-N

Air transport (ICAO-TI/IATA-DGR)**14.1. UN number or ID number:**

UN 3129

14.2. UN proper shipping name:

WATER-REACTIVE LIQUID, CORROSIVE, N.O.S. (CYCLOSILAZANES)

14.3. Transport hazard class(es):

4.3

14.4. Packing group:

II

Hazard label:

4.3+8



Special Provisions:

A3 A803

Limited quantity Passenger:

Forbidden

Passenger LQ:

Forbidden

Excepted quantity:

E0

IATA-packing instructions - Passenger:

Forbidden

IATA-max. quantity - Passenger:

Forbidden

IATA-packing instructions - Cargo:

481

IATA-max. quantity - Cargo:

5 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS:

No

Marine pollutant:

-

14.6. Special precautions for user

Warning: Flammable liquids! Vapours can form explosive mixtures with air.

In contact with water releases flammable gases. (Hydrogen, Ammonia (NH₃))**14.7. Maritime transport in bulk according to IMO instruments**

**Safety Data Sheet**

Revision: 22.07.2026

Rim Coat 365
Product code: SF10515

Page 12 of 14

not applicable

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 75

Directive 2010/75/EU on industrial emissions: < 75 %

Information according to Directive 2012/18/EU (SEVESO III): O3 Substances or mixtures with hazard statement EUH029

Additional information: P5c

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Water hazard class (D): 2 - obviously hazardous to water

Additional information

Observe in addition any national regulations!

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

**Rim Coat 365**

Revision: 22.07.2026

Product code: SF10515

Page 13 of 14

Abbreviations and acronyms

Water-react. 3: Substances and mixtures which in contact with water emit flammable gases, hazard category 3
Flam. Liq. 2: Flammable liquids, hazard category 2
Flam. Liq. 3: Flammable liquids, hazard category 3
Acute Tox. 3: Acute toxicity, hazard category 3
Acute Tox. 4: Acute toxicity, hazard category 4
Asp. Tox. 1: Aspiration hazard, hazard category 1
Skin Corr. 1B: Skin corrosion, sub-category 1B
Eye Dam. 1: Serious eye damage, hazard category 1
Skin Sens. 1: Skin sensitisation, hazard category 1
STOT SE 3: Specific target organ toxicity - single exposure, hazard category 3
Aquatic Chronic 3: Hazardous to the aquatic environment, long-term hazard category: Chronic 3
Aquatic Chronic 4: Hazardous to the aquatic environment, long-term hazard category: Chronic 4
CAS: Chemical Abstracts Service
CLP: Classification, Labelling and Packaging
EU: European Union
GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals
REACH: Registration, Evaluation and Authorization of Chemicals
UN: United Nations
PBT: Persistent, Bioaccumulative, Toxic
SVHC: Substance of Very High Concern
vPvB: very Persistent, very Bioaccumulative
ATE: Acute Toxicity Estimates
BCF: Bio-Concentration Factor
DMEL: Derived Minimal Effect Level
DNEL: Derived No Effect Level
PNEC: Predicted No Effect Concentration
VOC: Volatile Organic Compounds
DIN: Deutsches Institut für Normung e.V. (German Institute for Standardization)
EN: European Standard
ISO: International Organization for Standardization
IUCLID: International Uniform Chemical Information Database
LC50: Lethal Concentration, 50 %
LD50: Lethal Dose, 50 %
LL50: Lethal Loading, 50 %
OECD: Organisation for Economic Co-operation and Development
EC50: Effective Concentration 50 %
M-Faktor: Multiplication Factor
EL50: Effect Loading, 50 %
ErC50: Effective Concentration 50 %, growth rate
M-Faktor: Multiplication Factor
NOEC: No Observed Effect Concentration
ADN: Accord européen relatif au transport international des marchandises Dangereuses par voies de Navigation intérieures (European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways)
ADR: Accord européen sur le transport des marchandises Dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
DGR: Dangerous Goods Regulations
EmS: Emergency Schedules
IATA: International Air Transport Association
IBC: Intermediate Bulk Container
ICAO: International Civil Aviation Organization
IE: Industrial Emissions
IMDG: International Maritime Code for Dangerous Goods
LQ: Limited Quantity
MARPOL: International Convention for the Prevention of Marine Pollution from Ships

**Safety Data Sheet****Rim Coat 365**

Revision: 22.07.2026

Product code: SF10515

Page 14 of 14

MFAG: Medical First Aid Guide

RID: Regulations concerning the International carriage of Dangerous goods by rail

TI: Technical Instructions

Key literature references and sources for data

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations). (v.1.2, 2013)

Classification for mixtures and used evaluation method

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
Water-react. 3; H261	On basis of test data
Acute Tox. 4; H302	Calculation method
Skin Corr. 1B; H314	Calculation method
Eye Dam. 1; H318	Calculation method
Skin Sens. 1; H317	Calculation method
Asp. Tox. 1; H304	Calculation method
Aquatic Chronic 4; H413	Calculation method

Relevant H and EUH statements (number and full text)

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H261	In contact with water releases flammable gases.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H336	May cause drowsiness or dizziness.
H412	Harmful to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.
EUH014	Reacts violently with water.
EUH029	Contact with water liberates toxic gas.
EUH066	Repeated exposure may cause skin dryness or cracking.

Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)