

Hybrid Spray Wax

Wax polish spray for painted surfaces

Hybrid Spray Wax is a hybrid wax polish spray for all painted surfaces on automobiles, caravans and exterior surfaces of yachts. This special combination guarantees very simple and quick application.

It binds directly to the paint molecules, improves the dirt-repellent properties of the surface and forms a very thin, protective water-repellent film. The product can be used on dry and wet (with a minimal reduction in performance) surfaces. To achieve the best results, the surface to be sealed should be cool and dry.

Hybrid Spray Wax enhances the gloss and colour depth. You can also use the product as care for vehicles which are protected with our coat sealants. This will extend the lifetime of individual coatings. Ideal for care of exhibition vehicles, new vehicles, freshly prepared painted surfaces or after car washing.

Areas of application:

All smooth surfaces such as paint and plastics on automobiles, caravans or exterior surfaces of yachts

Properties:

- very water-repellent
- increased gloss and smoothness
- resistant to weak acids and bases
- simple and quick application
- minimal consumption

Application:

Shake the bottle and spray the product in a thin layer on the previously cleaned surface. Spread the product with the servFaces Premium Buffing Towel and let it dry briefly. Polish the surface afterwards until you achieve a high-gloss, streak-free result. Excess product or light streaks can be polished later with a fresh microfibre cloth (Premium Buffing Towel).

Caution: Do not apply the product in direct sunlight and do not let it dry!

Lifetime:

Hybrid Spray Wax provides protection for approx. 8 – 10 weeks. To obtain greater protection, you can apply an additional layer after 60 minutes.

Application temperature: +10°C to +35°C	Application quantity: 3 - 5 ml per m ²	Weatherproof after: 2 - 3 hours	Fully hardened after: 24 hours	pH resistance pH 3.0 - 10.5
Storage temperature +10°C to +25°C	Storage and shelf life: at least 12 months at ambient temperature in tightly sealed original container			

Caution: Protect the product from direct sunlight and freezing temperatures!

Note:

Emulsions and coating products need a certain time after application to bind to the surface and fully harden. Please therefore check the hardening time of individual products. This is the only way to guarantee that the product achieves the desired effect. Direct exposure of the surface to water or cleaning agents after application can considerably reduce the effect of the product.

**General information about product:**

Factors such as type of coating system, paint condition, product processing (preliminary cleaning, application temperature, curing time), etc., can influence the product's effectiveness and duration. Fluctuations of product properties cannot therefore be precluded.

Container sizes:

Art. No.:	Container:
SF10161	250 ml
SF10161.1	750 ml
SF10161.2	5 Litres

Accessories:

Premium Buffing Towels, Premium Allround Towels, Surface Cleaner Ultima, Surface Cleaner Neutra, Wash Concentrate

Note after use:

Surfaces treated with paint care products should generally always be cleaned as gently as possible to prevent damaging the product or even removing it. Avoid applying strong cleaning agents with a higher pH or a large content of solvents. We therefore recommend cleaning with a pH-neutral shampoo.

This product information should and can only be non-binding advice. It does not constitute any liability of the manufacturer. Before use, make sure that the product is suitable for your particular application.