

365 // Spray Coat

Hybrid spray sealant

servFaces 365 // Spray Coat is a hybrid spray sealant. The product is excellent for all painted surfaces on automobiles, motorcycles, campers and exterior surfaces of yachts. The very simple and quick application guarantees the best gloss results with intensive color rejuvenation.

It binds directly to the paint molecules, improves the surface dirt-repellent properties and forms a very thin, water-repellent protective film.

The very simple and quick application offers a broad area of applications suitable for professional as well as private users.

Areas of application:

All painted surfaces on automobiles, motorcycles, campers and exterior surfaces of yachts

Properties:

- Powerful water-repellent effects
- Enhanced gloss and smoothness
- Resistant to weak acids and bases
- Simple and quick application
- Minimal consumption
- Silicone oil-free

Use:

Clean the surface with Surface Cleaner Ultima followed by Surface Cleaner Neutra to neutralize it. Spray a thin layer of the product onto the surface (or directly onto a microfiber cloth) and polish until you achieve a high gloss and streak-free result. Excess material or moderate streaks should be removed immediately since the product crystallizes and therefore is impossible to remove later. Its fully hydrophobic properties develop in the first 6 - 8 hours.

Caution: Do not apply the product in direct sunlight and do not let it dry!

Lifetime:

365 // Spray Coat provides protection for up to 365 days. To obtain a greater protection layer, an additional layer can be applied after 30 - 60 minutes. Regular aftercare with Hybrid Spray Wax, Hydro Seal or Wet Seal & Care extends the lifetime as well.

Application temperature: +5°C to +40°C	Consumption: 3 - 5 ml per m ²	Weatherproof: after 4 - 6 hours	Fully cured after: 24 hours	pH resistance pH 3.0 – 11.0
Storage temperature +10°C to +25°C	Storage and shelf life: At least 18 months at ambient temperature in tightly sealed original container			

Caution: Protect the product from direct sunlight and freezing temperatures!

**Note:**

Emulsions and coating products need a certain period of time to bind to the surface and fully cure after application. Therefore, please check the curing time of individual products. Only this can guarantee that the product provides the desired benefits. Direct exposure of the surface to water or cleaning agents after application can considerably reduce the product's properties.

General information about the product:

Factors such as type of coating system, paint condition, product processing (preliminary cleaning, application temperature, curing time), etc., can influence the product's effectiveness and lifetime. Therefore, fluctuations of product properties cannot be excluded.

Container sizes:

Art. No.:	Container:
SF10278.1	75 ml
SF10278	250 ml

Accessories:

Surface Cleaner Ultima, Surface Cleaner Neutra, Special Coating Towels, Premium Buffing Towels, Wash Concentrate

Note after use:

Surfaces treated with paint care products should principally always be cleaned as gently as possible to avoid damaging or even removing the product properties. Avoid using strong cleaning agents with high pH or a high content of solvents. We therefore recommend cleaning with a pH-neutral shampoo.

This product information should and can only be taken as non-binding advice. The manufacturer does not accept any liability whatsoever. Before use, make sure that the product is suitable for your particular application.